



LED 1097

12 V


Surface-mounted light 12 V, 8 W


 $\bigcirc A^+$ 

2

12/24 V







> Dimmable:	Yes
> Area of application:	For bathroom and living roo Mirror and cabinet lighting Suitable for retrofitting
> Housing material:	Stainless steel
> Housing colour/finish:	Glossy
> Plinth material:	Steel
> Plinth colour/finish:	Chrome plated
> Diffuser material:	Acrylic glass
> Diffuser colour/finish:	Matt
> Plug drill hole diameter:	8 mm
> Life time:	30000 h
> Colour rendering index Ra:	≥80
> Weighted energy consumption:	8.8 kWh/1000 h
> Energy efficiency class:	A+
> Mounting:	For screw fixing
<b>Supplied with</b> 1 light with 2 m lead	

> Homogeneous and bright illumination

> High-quality optics due to acrylic glass diffuser

4000 K	65°
1390 Ix	🔆 + 250 mm
545 lx	
220 lx	
55 lx	🔆 – 1000 mm

				IP20 🔍
Colour temperature K	Light colour	Wattage W	Length mm	Glossy
4000	Cool white	8	600	833.02.450
Packing: 1 piece				
Adapter		Pack	ing	Cat. No.
<b>12V</b> 5 <b>12V</b> Adapter required for connection to the drivers or distributors of the Loox5 system			ce	833.95.823

ightarrow Häfele Loox5 12 V driver set with 6-way distributor

5 12V 230V ·⊷∎:	Supplied with	
	1 driver	Distributor
	1 6-way distributor 1 mains lead 2 m with flat Euro plug	With switch
		Häfele Con
	Luio piug	Packing: 1 s

Distributor version	20 W	40 W
With switching function	833.74.653	833.74.654
Häfele Connect Mesh 8	833.74.650	833.74.651
Packing: 1 set		

► MB 2.390 • Installation rules in bathrooms in residential areas