

PRODUCT SHEET

Description:

Mini Glass Door Hinge NPL, Half-Overlay, Soft Close, W/Clip On Plate F/Chipboard Screws, H=0, 95DG, Bore:Ø26mm, W/SISO, DK Name Plate, No Cover Cap & Screws, 4-6mm Glass Thickness

Item number:

15.01.721-0

Units	Box	Carton	HS Code	Barcode
Pcs.	1	100	8302100090	
				5704866052436



Steel - Nickel Plated	Item No.	D: Overlay calculations	A: Gap between door and side panel	L: Gap between door and carcass																																																
Full overlay (A)  	15.01.720 Incl. SISO name plate + mounting plate H = 0	<table><tr><th>D</th><th>K</th><th>4</th><th>5</th><th>6</th><th>7</th></tr><tr><td>1</td><td>14.5</td><td>15.5</td><td>16.5</td><td>17.5</td><td></td></tr><tr><td>2</td><td>12.5</td><td>13.5</td><td>14.5</td><td>15.5</td><td></td></tr><tr><td>4</td><td>10.5</td><td>11.5</td><td>12.5</td><td>13.5</td><td></td></tr></table>	D	K	4	5	6	7	1	14.5	15.5	16.5	17.5		2	12.5	13.5	14.5	15.5		4	10.5	11.5	12.5	13.5		<table><tr><th>L</th><th>K</th><th>4</th><th>5</th><th>6</th><th>7</th></tr><tr><td>1</td><td>0</td><td>0</td><td>1</td><td>1</td><td>2</td></tr><tr><td>2</td><td>0</td><td>0</td><td>1</td><td>1</td><td>2</td></tr><tr><td>4</td><td>0</td><td>0</td><td>1</td><td>1</td><td>2</td></tr></table>	L	K	4	5	6	7	1	0	0	1	1	2	2	0	0	1	1	2	4	0	0	1	1	2	
D	K	4	5	6	7																																															
1	14.5	15.5	16.5	17.5																																																
2	12.5	13.5	14.5	15.5																																																
4	10.5	11.5	12.5	13.5																																																
L	K	4	5	6	7																																															
1	0	0	1	1	2																																															
2	0	0	1	1	2																																															
4	0	0	1	1	2																																															
Half overlay (B)  	15.01.721 Incl. SISO name plate + mounting plate H = 0	<table><tr><th>D</th><th>K</th><th>4</th><th>5</th><th>6</th><th>7</th></tr><tr><td>1</td><td>5.5</td><td>6.5</td><td>7.5</td><td>8.5</td><td></td></tr><tr><td>2</td><td>3.5</td><td>4.5</td><td>5.5</td><td>6.5</td><td></td></tr><tr><td>4</td><td>1.5</td><td>2.5</td><td>3.5</td><td>4.5</td><td></td></tr></table>	D	K	4	5	6	7	1	5.5	6.5	7.5	8.5		2	3.5	4.5	5.5	6.5		4	1.5	2.5	3.5	4.5		<table><tr><th>L</th><th>K</th><th>4</th><th>5</th><th>6</th><th>7</th></tr><tr><td>1</td><td>0</td><td>0</td><td>1</td><td>1</td><td>2</td></tr><tr><td>2</td><td>0</td><td>0</td><td>1</td><td>1</td><td>2</td></tr><tr><td>4</td><td>0</td><td>0</td><td>1</td><td>1</td><td>2</td></tr></table>	L	K	4	5	6	7	1	0	0	1	1	2	2	0	0	1	1	2	4	0	0	1	1	2	
D	K	4	5	6	7																																															
1	5.5	6.5	7.5	8.5																																																
2	3.5	4.5	5.5	6.5																																																
4	1.5	2.5	3.5	4.5																																																
L	K	4	5	6	7																																															
1	0	0	1	1	2																																															
2	0	0	1	1	2																																															
4	0	0	1	1	2																																															
Inset (C)  	15.01.722 Incl. SISO name plate + mounting plate H = 0	<table><tr><th>A</th><th>K</th><th>4</th><th>5</th><th>6</th><th>7</th></tr><tr><td>1</td><td>4.5</td><td>5.5</td><td>6.5</td><td>7.5</td><td></td></tr><tr><td>2</td><td>6.5</td><td>7.5</td><td>8.5</td><td>9.5</td><td></td></tr></table>	A	K	4	5	6	7	1	4.5	5.5	6.5	7.5		2	6.5	7.5	8.5	9.5		<table><tr><th>L</th><th>K</th><th>4</th><th>5</th><th>6</th><th>7</th></tr><tr><td>1</td><td>0</td><td>0</td><td>1</td><td>1</td><td>2</td></tr><tr><td>2</td><td>0</td><td>0</td><td>1</td><td>1</td><td>2</td></tr><tr><td>4</td><td>0</td><td>0</td><td>1</td><td>1</td><td>2</td></tr></table>	L	K	4	5	6	7	1	0	0	1	1	2	2	0	0	1	1	2	4	0	0	1	1	2							
A	K	4	5	6	7																																															
1	4.5	5.5	6.5	7.5																																																
2	6.5	7.5	8.5	9.5																																																
L	K	4	5	6	7																																															
1	0	0	1	1	2																																															
2	0	0	1	1	2																																															
4	0	0	1	1	2																																															
 	H = 0 Chipboard screws Clip-on	Delivered as standard mounting plate with all hinges. Chipboard screws to be ordered separately.																																																		
 	15.03.724-0 H = 0 Euro screws Clip-on	To be ordered separately if easy up & down adjustment is wanted. Pre-mounted euro screws included.																																																		

Cup drawing



Opening angle:	95°
Depth of hinge cup:	10.6 mm
Diameter of hinge cup:	26 mm
Possible drilling distances on the glass door (K):	4.7 mm
Glass door thickness:	4-6 mm

SISO A/S

Mileparken 11
DK-2740 Skovlunde
Denmark
VAT: DK 24786013

Phone +45 45 830 900

www.siso.dk
siso@siso.dk

Danske Bank
Nytrov Branch
Copenhagen
SWIFT: DABADKKK

Account no.
4180 3112 112936
IBAN Account
DK7230003112112936