

Steel wheel suspension



Polyamide



Rubber



Beech,
grey running surface




Polyurethane,
transparent running surface




Plastic,
black running surface



Beech,
black running surface



Threaded bolt,
steel galvanized



Mounting plate,
steel galvanized



- Finish: Wheel suspension: Chrome plated
- Load bearing capacity: approx. 50 kg per castor
- Version: Free running, without brake

Installation	Dimensions mm	Wheel diameter mm	Wheel width mm	Installation height mm	Running surface	Finish/colour	Cat. No.
Polyamide wheel							
Threaded bolt	M8 x 15	50	18	78	Hard	Black	661.52.310
Mounting plate	42 x 42	50	18	82	Hard	Black	661.52.300
Rubber wheel							
Threaded bolt	M8 x 15	50	18	78	Soft	Grey	661.52.510
Mounting plate	42 x 42	50	18	82	Soft	Grey	661.52.500
Beech wheel, grey running surface							
Threaded bolt	M8 x 15	50	18	78	Soft	Cherry wood coloured Lacquered	661.53.610 661.53.310
Mounting plate	42 x 42	50	18	82	Soft	Cherry wood coloured Lacquered	661.53.600 661.53.300
Polyurethane wheel							
Threaded bolt	M10 x 15	80	20	118	Soft	Black	661.50.411
Mounting plate	60 x 60	80	20	125	Soft	Black	661.50.401
Plastic wheel							
Threaded bolt	M10 x 15	80	12	118	Soft	Translucent Orange translucent Green translucent	661.49.411 661.49.911 661.49.011
Mounting plate	60 x 60	80	12	125	Soft	Translucent Orange translucent Green translucent	661.49.401 661.49.901 661.49.001
Beech wheel, black running surface							
Threaded bolt	M10 x 15	80	12	118	Soft	Cherry wood coloured Lacquered	661.51.611 661.51.311
Mounting plate	60 x 60	80	12	125	Soft	Cherry wood coloured Lacquered	661.51.601 661.51.301

Packing: 4 pieces

Furniture glide with internal thread ▶ FF 10.23

Screw-in sleeve ▶ FF 10.37